

# Spreader calibrations - OEN 46%

The spreader settings below are for guidance only. The exact fertiliser rates and spreading patterns using these settings cannot be guaranteed as the application will be affected by the condition of the spreader itself and the environmental conditions at the time of application.

To ensure greater accuracy, the spreader should be recalibrated for application rate and spread pattern using a tray test. Up to date information can be found on the spreader manufacturers website.

Product Name	Spreader (Make/Model)	Spread Width (m)	Disc/Vane Type	Spreader Height	Tilt (°)	PTO /Disc speed (rpm)	Vane setting / Drop on point/ Discharge point	Application Rate (kg/Ha)	Forward speed (km/h)
OEN 46N	Amazone ZAM	24	OS 20-28	80		540	70/87	250	10
OEN 46N	Amazone ZAM	24	OM 18-24	80		540	20/47	250	10
OEN 46N	Amazone ZAM	24	OM 24-36	80		540	16/41	250	10
OEN 46N	Amazone ZAM	32	OM 24-36	80		540	16/51	250	10
OEN 46N	Kuhn Axis 30.1	24	S4	50		540	6.5	250	10
OEN 46N	Kuhn Axis 30.1	32	S8	50		540	9.5	250	10
OEN 46N	KRM Ex Trend	24	E6T	85	4°	540	Pos 1 & 2	250	10
OEN 46N	KRM Ex Trend	32	E8T	95	6°	540	Pos 1 & 2	250	10
OEN 46N	Sulky X36	24	12/28	70		540	126	250	10
OEN 46N	Sulky X36	24	24/36	70		540	119	250	10
OEN 46N	Sulky X36	28	24/36	70		540	121	250	10

Machine equivalents:

Amazone ZAM : 1200,1500, Compact, Novis, Maxis, Max; Kuhn Axis 30.1: 40.1; KRM Ex Trend : M2, M3; Sulky X36 : X44

Advanced nutrition for enhanced performance

t: 03333 239 230

e: [productenquiry@originfertilisers.co.uk](mailto:productenquiry@originfertilisers.co.uk)

[www.originfertilisers.co.uk](http://www.originfertilisers.co.uk)